THICKNESS METER

PCE-TG 150A



- **Measured value memory for 1500 values**
- **Calibration reference on housing**
- **Automatic switch-off**
- **Material thickness measurement up to 300 mm**
- **Battery status display**
- **Optional with ISO calibration certificate**

The thickness meter can measure material thicknesses up to 300 mm. To ensure that the material thickness of a wide variety of homogeneous materials can be measured, it is possible to store the corresponding sonic velocity in the thickness meter. For materials such as steel, aluminium, zinc, silver and gold, the appropriate sonic velocities are already stored in the device library. This means that the thickness meter can be used universally.

Individual maximum and minimum values can be stored with the thickness meter's limit value function. If the measured value of the test specimen is outside the limits, the thickness meter signals this visually. If required, the thickness meter can also provide acoustic signalling in addition to the visual display. The thickness meter is therefore used, for example, in quality assurance and incoming goods inspection.

The thickness meter has a data memory on which the measured values can be recorded. After a measurement process, the stored measured values can be analysed directly on the thickness meter. The stored data is displayed graphically by the thickness meter. In addition, each individual measuring point can be approached and read in the graphic of the thickness meter. To simplify the analysis of the measured values, the average, the largest and smallest measured values are displayed on the thickness meter. The thickness meter can optionally be equipped with an ISO calibration certificate.

Specification

Material thickness	
Measuring range	1 ... 99,99 mm
Resolution	0,01 mm
Accuracy	±0.5 % of Rd +0.05 mm
Material thickness	
Measuring range	100 ... 300 mm
Resolution	0,1 mm
Accuracy	±0.5 % of Rd +0.05 mm
Sensor	
Designation	PCE-TG 5M10d
Battery type	Ultrasound
Frequency	5 MHz
Temperature range	-10 ... 60 °C
Measurable materials	Steel, aluminium, zinc, silver, gold, metal, plastic, ceramic, glass, other homogeneous materials
Minimum diameter of pipes	30 mm
Additional description	Standard probe for flat materials
Dimension	Ø 10 mm x 23.4 mm
Sensor	
Designation	PCE-TG 5M6d
Measuring range	1 ... 50 mm
Battery type	Ultrasound
Frequency	5 MHz
Temperature range	-10 ... 60 °C
Measurable materials	Steel, aluminium, zinc, silver, gold, metal, plastic, ceramic, glass, other homogeneous materials
Minimum diameter of pipes	20 mm
Additional description	Standard probe for flat materials
Dimension	Ø 6 mm x 25.3 mm

General technical data	
Units	mm
Display type	TFT colour display
Display size	2,4 in
Storage medium	Internal memory
Storage capacity	1500 Values
Automatic power-off from...to	2 ... 30 min.
Adjustable sound velocity	1000 ... 9999 m/s
Menu language	English, Chinese
Protection class (device)	IP52
(Rechargeable) battery	3 x 1,5 V AA battery , Alkali-manganese
Capacity	3000 mAh
Performance	4,5
Operating conditions	0 ... 40 °C , 0 ... 90 % RH
Storage conditions	0 ... 40 °C , 0 ... 90 % RH
Dimensions (L x W x H)	168 x 87 x 35 mm
Weight	230 g

PCE Instruments UK Ltd.
Chester Rd, Old Trafford Suite 1N-B, Trafford House, M32 0RS Manchester
Great Britain

Phone: +44 (0) 161 4649020
info@pce-instruments.co.uk