

# KERN DIS 100-3



High-precision moisture analyzer for demanding analyses



## Category

Brand	KERN
Product category	Laboratory balance
Product group	Moisture analyzer
Product family	DIS

## Measuring System

Weighing system	Force compensation
Weighing capacity [Max]	120 g
USP Minimum weight of sample (k = 2, U = 0.1%)	2 g
Readability [d]	0,001 g
Reproducibility	0,001 g
Linearity	± 0,003 g
Minimum weight [Min] (verifiable)	0,2 g
Resolution	120.000
Adjustment options	Adjusting with external weight
Recommended adjusting weight	100 g (F1)
Possible calibration points	100 g
Stabilization time	3 s
Eccentric loading at 1/3 [Max]	0,005 g
Reproducibility weight of sample 10 g	0,03%
Temperature increment	1 °C
Construction type of the scale	Single-range balance
Reproducibility weight of sample 2 g	0,1%

Units	g % Humidity % Dry mass %M ATRO Grams/Liter
-------	---

	% R (ratio) %D ATRO
Units (if device is conformity assessed)	g
Temperature [Min] (°C)	30 °C
Temperature [Max] (°C)	175 °C
Readability moisture [d] (%)	0,001%
Maximum creep (15 minutes)	10 mg
Maximum creep (30 minutes)	20 mg
Default unit	g
Temperature calibration points	100 °C; 175 °C

## Display

Display type	LCD graphic
Display backlight	✓
Display screen size	132×38 mm
Display digit height - smallest digit	5 mm
Display digit height	15 mm
Languages of the user interface	English

## Construction

Dimensions completely mounted (W×D×H)	211×342×187 mm
Dimensions weighing surface (Ø)	95 mm
Dimensions weighing surface	95 mm
Material housing	ABS plastic
Material weighing plate	aluminium
Material display housing	plastic
Material load cell(s)	aluminium
Material substructure	plastic
Level indicator	✓
Levelling feet adjustable	✓
Heat generation capacity (W)	415
Cable length	1,8 m

## Functions

Tolerance weighing - type of signal	visual
Underfloor weighing	None
Capacity - Display	✓
Standby function	✓
Drying modes	Standard drying Rapid drying Gentle drying Drying in levels
Memory - number of drying programs	40

# KERN DIS 100-3

# KERN

High-precision moisture analyzer for demanding analyses

Switch-off criteria	time controlled automatic manual
Memory function	✓
Memory - number of results	1.000
Memory - number of sample (descriptions)	1.000
Auto-off interval(s) in mains power mode	1 min - 99 min
Tare function	manual (multi)
Number of keys for operation	24

## Interface

Interfaces	RS-232 standard USB-Device
------------	-------------------------------

## Power Supply

Supplied power supply	Power supply unit
Power supply type	Built-in power supply
Plug-in power supply / adapter for countries - included with the delivery	EURO CH
Plug-in power supply / adapter for countries - optional	UK
Input voltage power supply / power [Max]	230 V AC, 50 Hz
Power supply cable removable	removable
Input voltage device / power [Max]	230 V AC, 50 Hz
Power socket for mains adapter	Power supply cable

## Environmental conditions

Ambient temperature [Min]	15 °C
Ambient temperature [Max]	30 °C
Humidity of environment [Min]	25 %
Humidity of environment [Max]	85 %
Storage temperature [Min]	-10 °C
Storage temperature [Max]	50 °C

## Approval

CE mark	✓
---------	---

## Services (optional)

Article number for DAkkS calibration	963-127
Article number for factory calibration (temperature)	964-305
Article number for certificate of conformity	969-517

## Packing & Shipping

Delivery time	1 d
Dimensions packaging (W×D×H)	325×390×285 mm
Shipping method	Parcel service
Net weight approx.	5,0 kg
Gross weight approx.	5,0 kg
Shipping weight	7,2 kg
Shipping volume weight	7,2 kg

## Product information

GTIN/EAN number	404576 1492981
Trade number	90160010
REACH classification	no prohibited substances

## Pictograms

### STANDARD



### OPTION

